


# DC-733i

7.0 MegaPixel

- ▶ 7.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 2.5" TFT LCD display
- ▶ Video function
- ▶ 15 scene modes
- ▶ Movie recording with sound
- ▶ USB 2.0 high speed connect



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-733i and certified with its logo a rating of 'GOOD'. In detail:

- Handling:	Grade 1,0
- Workmanship:	Grade 1,0
- Instruction manual:	Grade 2,2



- Handling tested
- Workmanship tested
- Instruction manual tested

# DC-733i

## Technical details

### ► Image sensor

Sensor	7.0 megapixel CCD
--------	-------------------

### ► Optics

Lens and type	6 elements in 5 groups, 3x continuous zoom
Focal length	f = 5.8 (W) ~ 17.4 (T) mm
Equivalent to 35mm camera	35 (W) ~ 105 (T) mm)
Brightness	F/ 2.8 (W), 4.9 (T)
Shutter speed	1/2000 ~ 8 sec.

### ► Zoom

Digital zoom	4x
Optical zoom	3x

### ► Focusing

Focus range	80cm~Infinity, macromode: 15 cm~1m
-------------	------------------------------------

### ► Exposure

Exposure compensation	-2 EV to +2 EV in 1/3 step, [-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0]
Exposure meter	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400
White balance	Auto, daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Exposure control	Automatic/ manual

### ► LCD

Colour	2.5" TFT LCD, 640 x 240
--------	-------------------------

### ► Memory

Memory internal	16 MB
Memory external	SD (up to 2 GB), SDHC (up to 4 GB)

### ► Resolution

Still image	3072 x 2304, (3:2) 3072 x 2048, (16:9) 3072 x 1728, 2560 x 1920, 2048 x 1536, 1024 x 768, 640 x 480
Video	640 x 480, 320 x 240, 160 x 120, 30 fps

### ► File formats

Still image	JPEG, EXIF 2.2 compatible format DCF compatible. Support DPOF
Video	AVI w/ audio
Audio	WAV

### ► Scene mode

Scene mode	Program, movie, voice REC, portrait, landscape, sunset, night scene, text, back light, kids, snow, food, fireworks, building, quick mode
------------	--

### ► Flash modes

Flash light	Auto, red eye reduction, slow sync., on /off effective distance: 2.5 m (W), 1.5 m (T)
-------------	---

### ► Interface

USB	2.0
TV out	PAL / NTSC

### ► Power source

Power supply	2x AA Alkaline batteries
Auto power off	1 min, 3 min, 5 min

### ► Others

Camera dimensions	88 x 60 x 23 mm
Housing	Highend plastic
Weight	116 g

### ► Accessories

	USB cable, Video cable, pouch, 2 AA Alkaline batteries, hand strap, CD software
--	---

### ► Logistik

Item number	06843
Barcode	4004781068439
Packaging size	8.7 x 16.1 x 22.5 cm
Packaging unit	5
Weight (packaging)	898g
Weight (packaging unit))	5.1 kg
Dimensions packing unit	25 x 46 x 19 cm

Dealer stamp

AGFAPHOTO is used under license of Agfa-Gevaert AG. Agfa-Gevaert AG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, [www.agfaphotocameras.com](http://www.agfaphotocameras.com)  
Manufactured by plawa-feinwerktechnik GmbH & Co. KG, [www.plawa.com](http://www.plawa.com)