


DC-733i

7.0 MegaPixel

- ▶ 7.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 2.5" TFT LCD display
- ▶ Video function
- ▶ 15 scene modes
- ▶ Movie recording with sound
- ▶ USB 2.0 high speed connect



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-733i and certified with it's logo a rating of 'GOOD'. In detail:

- Handling:	Grade 1,0
- Workmanship:	Grade 1,0
- Instruction manual:	Grade 2,2



- Handling tested
- Workmanship tested
- Instruction manual tested

DC-733i

Technical details

► Capteur d'images

Capteur	7.0 megapixel CCD
---------	-------------------

► Objectif

Objectif et construction	6 elements in 5 groups, 3x continuous zoom
Longueur focale	f = 5.8 (W) ~ 17.4 (T) mm
Équivalence caméra 35mm	35 (W) ~ 105 (T) mm)
Vitesse de l'objectif	F/ 2.8 (W), 4.9 (T)
Temps d'obturation	1/2000 ~ 8 sec.

► Zoom

Zoom optique	4x
Zoom numérique	3x

► Mise au point

Focale	80cm~Infinity, macromode: 15 cm~1m
--------	------------------------------------

► Exposition

Correction d'exposition	-2 EV to +2 EV in 1/3 step, [-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0]
Variantes d'exposition	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400
Ance des blancs	Auto, daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Système de mesure de la lumière	Automatic/ manual

► Ecran

Ecran LCD	2.5" TFT LCD, 640 x 240
-----------	-------------------------

► Mémoire

Mémoire interne	16 MB
Mémoire externe	SD (up to 2 GB), SDHC (up to 4 GB)

► Résolution

Clichés	3072 x 2304, (3:2) 3072 x 2048, (16:9) 3072 x 1728, 2560 x 1920, 2048 x 1536, 1024 x 768, 640 x 480
Vidéo	640 x 480, 320 x 240, 160 x 120, 30 fps

► Navigations-Features

Clichés	JPEG, EXIF 2.2 compatible format DCF compatible. Support DPOF
Vidéo	AVI w/ audio
Audio	WAV

► Mode de scène

Mode continu	Program, movie, voice REC, portrait, landscape, sunset, night scene, text, back light, kids, snow, food, fireworks, building, quick mode
--------------	------------------------------------------------------------------------------------------------------------------------------------------

► Fonctions flash

Flash	Auto, red eye reduction, slow sync., on /off effective distance: 2.5 m (W), 1.5 m (T)
-------	------------------------------------------------------------------------------------------

► Interfaces

USB	2.0
Sortie TV	PAL / NTSC

► Alimentation

Alimentation	2x AA Alkaline batteries
Alimentation	1 min, 3 min, 5 min

► Divers

Dimesions d'appareil-photo	88 x 60 x 23 mm
Boîtier	Highend plastic
Poids	116 g

► Accessoires

	USB cable, Video cable, pouch, 2 AA Alkaline batteries, hand strap, CD software
--	---------------------------------------------------------------------------------

► Logistique

Réf. article	06843
Code EAN	4004781068439
Emballage de l'appareil photo	8,7 x 16.1 x 22.5 cm
Unité de conditionnement	5
Poids (emballage)	898g
Poids / UC	5.1 kg
Dimensions/ UC	25 x 46 x 19 cm

Cachet du revendeur

AGFAPHOTO is used under license of Agfa-Gevaert AG. Agfa-Gevaert AG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, www.agfaphotocameras.com
Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com