

## DC-733i

## 7.0 MegaPixel

- 7.0 MegaPixel CCD sensor
- 3x optical zoom, 4x digital zoom
- 2.5" TFT LCD display
- Video function
- 15 scene modes
- Movie recording with sound
- USB 2.0 high speed connect



















TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-733i and certified with it's logo a rating of 'GOOD'. In detail:

- Handling: Grade 1,0
- Workmanship: Grade 1,0
- Instruction manual: Grade 2,2



- Handling tested
- Workmanship tested
- Instruction manual tested



## DC-733i

## **Technical details**

Image sensor		Flash modes	
Sensor	7.0 megapixel CCD	Flash light	Auto, red eye reduction, slow sync., on /o effective distance:
Optics			2.5 m (W), 1.5 m (T)
Lens and type	6 elements in 5 groups, 3x continuous		
	zoom	► Interface	
Focal length	f = 5.8 (W) ~ 17.4 (T) mm	USB	2.0
Equivalent to 35mm camera	35 (W) ~ 105 (T) mm)	TV out	PAL / NTSC
Brightness	F/ 2.8 (W), 4.9 (T)		
Shutter speed	1/2000 ~ 8 sec.	Power source	
		Power supply	2x AA Alkaline batteries
Zoom		Auto power off	1 min, 3 min, 5 min
Digital zoom	4x		
Optical zoom	3x	▶ Others	
		Camera dimensions	88 x 60 x 23 mm
► Focusing		Housing	Highend plastic
Focus range	80cm~Infinity, macromode: 15 cm~1m	Weight	116 g
► Exposure		Accessories	
Exposure compensation	-2 EV to +2 EV in 1/3 step, (-2.0, -1.7,		USB cable, Video cable, pouch, 2 AA
	-1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0,		Alkaline batteries, hand strap,
	+1.3, +1.7, +2.0)		CD software
Exposure meter	Center-weighted, multi, spot		
ISO	Auto, 50, 100, 200, 400		
White balance	Auto, daylight, cloudy, tungsten, fluore-		
	scent_H, fluorescent_L, customer		
Exposure control	Automatic/ manual	► Logistik	
		Item number	06843
► LCD		Barcode	4004781068439
Colour	2.5" TFT LCD, 640 x 240	Packaging size	8.7 x 16.1 x 22.5 cm
		Packaging unit	5
► Memory		Weight (packaging)	898g
Memory internal	16 MB	Weight (packaging unit))	5.1 kg
Memory external	SD (up to 2 GB), SDHC (up to 4 GB)	Dimensions packing unit	25 x 46 x 19 cm
Resolution			
Still image	3072 x 2304, (3:2) 3072 x 2048, (16:9)		
, and the second	3072 x 1728, 2560 x 1920, 2048 x 1536,	Dealer stamp	
	1024 x 768. 640 x 480	,	
Video	640 x 480, 320 x 240, 160 x 120, 30 fps		
► File formats			
Still image	JPEG, EXIF 2.2 compatible format		
Juli illage	DCF compatible. Support DPOF		
Video	AVI w/ audio		
Audio	WAV		
Addio	VVAV		
Scene mode			
Scene mode	Program, movie, voice REC, portrait,		fa-Gevaert AG. Agfa-Gevaert AG does not manufacture this pr
	landscape, sunset, night scene, text,		support. For service, support and warranty information, contain brands and product names are registered trademarks of the
	back light, kids, snow, food, fireworks,		echnical features can be changed without notice.

building, quick mode

AgfaPhoto Holding GmbH, www.agfaphotocameras.com Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com