

DC-8330i

8.0 MegaPixel

- ▶ 8.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 3.0" TFT-LCD (230K), 960 x 240 dots
- ▶ 21 scene modes

Highlights

- ▶ ASM (Aperture priority, Shutter priority, Manual exposure mode)
- ▶ Photo stabilizer
- ▶ Face Tracking
- ▶ ISO 1600
- ▶ SDHC compatible (4 GB)
- ▶ AF lamp
- ▶ Histogram



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-8330i and certified with it's logo a rating of 'GOOD'. In detail:

- Handling:	EXCELLENT
- Workmanship:	GOOD
- Instruction manual:	GOOD



- Handling tested
- Instruction manual tested
- Workmanship tested

DC-8330i

Technische Daten

► Bildsensor	
Sensor	8.0 MegaPixel CCD
► Objektiv	
Linse und Aufbau	6 elements in 5 groups, (incl. 3 pcs aspherical)
Brennweite	f = 6.2 (W) ~ 18.6 (T) mm
Equivalent 35mm Kamera	37.5 (W) ~ 112.5 (T) mm
Lichtstärke	F/2.8 (W), F/5.2 (T)
Verschlusszeit	1/2000 ~ 8 sec.
► Zoom	
Digitalzoom	4x
Optischer Zoom	3x
► Fokussierung	
Fokus Reichweite	T: 40 cm ~ Infinity, W: 15 cm ~ Infinity
► Belichtung	
Belichtungsausgleich	-2EV to +2EV in 1/3 step, (-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0)
Belichtungsvariante	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400, 800, 1600
Weißausgleich	Daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Belichtungskontrolle	Automatic/manual
► Sucher / Monitor	
Farbdisplay	3.0" TFT-LCD, 960 x 240 dots
► Speicher	
Interner Speicher	16 MB
Externer Speicher	2GB (SD-card) and 4GB (SDHC)
► Auflösung	
Bilder	3264 x 2448 (default), 3264 x 2176 (3:2), 3200 x 1800 (16:9), 2816 x 2112, 2304 x 1728, 1600 x 1200, 640 x 480
Video	848 x 480 (16:9), 640 x 480, 320 x 240, 30 fps
► Dateiformat	
Bilder	JPEG, EXIF 2.2, support DPOF, PictBridge compatible
Video	AVI
Audio	WAV
► Motivmodus	
Motivmodus	Sunset, snow, soft skin, sports, soft flowing water, backlight, building, movie, portrait, party, fireworks, food, night scene, night scene portrait, Q mode, landscape, kids, text, candle, voice Rec, program

► Blitzfunktion	
Blitzlicht	Auto, auto w/Red-eye reduction, slow sync. w/Red-eye reduction, forced On, Off; flash range: 2.3 m (W), 1.3 m (T)
► Verbindung / Anschluss	
USB	2.0
TV out	PAL/NTSC
► Stromversorgung	
Stromversorgung	2x AA Alkaline batteries
Auto. Abschalten	1 min., 3 min., 5 min.
► Sonstiges	
Produkt Abmessung	approx. 95 x 61 x 24 mm (W x H x L)
Gehäuse	Highend plastic
Gewicht	146 g (w/o batteries)
Menü-Sprache	English, German, Spanish, French, Italian, Portuguese, Dutch, Swedish, Greek, Czech, Polish, Turkish, Hungarian, Russian, Arabic, Romanian, Thai, Japanese, Simple Chinese, Korean, Traditional Chinese
► Zubehör	
	USB cable, AV cable, 2 x AA batteries, wrist strap, pouch, CD-Rom
► Logistik	
Artikelnummer	06852
EAN code	4004781068521
Kamera Verpackung	8.7 x 16.1 x 22.5 cm (W x H x L)
Verpackungseinheit	5
Gewicht (Verpackung)	approx. 706 g
Gewicht/VPE	approx. 4,1 kg
Abmessung VPE	19 x 25 x 46 cm (W x H x L)

Händlerstempel

AgfaPhoto is used under license of Agfa-Gevaert NV&Co. KG. Agfa-Gevaert NV&Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.