

DC-8330i

8.0 MegaPixel

- ▶ 8.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 3.0" TFT-LCD (230K), 960 x 240 dots
- ▶ 21 scene modes

Highlights

- ▶ ASM (Aperture priority, Shutter priority, Manual exposure mode)
- ▶ Photo stabilizer
- ▶ Face Tracking
- ▶ ISO 1600
- ▶ SDHC compatible (4 GB)
- ▶ AF lamp
- ▶ Histogram



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-8330i and certified with it's logo a rating of 'GOOD'. In detail:

- Handling:	EXCELLENT
- Workmanship:	GOOD
- Instruction manual:	GOOD



- Handling tested
- Instruction manual tested
- Workmanship tested

DC-8330i

Dati tecnici

► Sensore immagine

Sensore	8.0 MegaPixel CCD
---------	-------------------

► Obiettivo

Lente e tipo	6 elements in 5 groups, (incl. 3 pcs aspherical)
Distanza focale	f = 6.2 (W) ~ 18.6 (T) mm
Equivalente fotocamera 35 mm	37.5 (W) ~ 112.5 (T) mm
Luminosità	F/2.8 (W), F/5.2 (T)
Velocidad de obturación	1/2000 ~ 8 sec.

► Zoom

Zoom digitale	4x
Zoom ottico	3x

► Messa a fuoco

Campo di messa a fuoco	T: 40 cm ~ Infinity, W: 15 cm ~ Infinity
------------------------	---

► Esposizione

Compensazione esposizione	-2EV to +2EV in 1/3 step, (-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0)
Varianti di esposizione	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400, 800, 1600
Bilanciamento del bianco	Daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Controllo esposizione	Automatic/manual

► Mirino / Monitor

Display	3.0" TFT-LCD, 960 x 240 dots
---------	------------------------------

► Memoria

Memoria interna	16 MB
Memoria esterna	2GB (SD-card) and 4GB (SDHC)

► Risoluzione

Immagini	3264 x 2448 (default), 3264 x 2176 (3:2), 3200 x 1800 (16:9), 2816 x 2112, 2304 x 1728, 1600 x 1200, 640 x 480
Video	848 x 480 (16:9), 640 x 480, 320 x 240, 30 fps

► Formati file

Immagini	JPEG, EXIF 2.2, support DPOF, PictBridge compatible
Video	AVI
Audio	WAV

► Modo di scena

Modo di scena	Sunset, snow, soft skin, sports, soft flowing water, backlight, building, movie, portrait, party, fireworks, food, night scene, night scene portrait, Q mode, landscape, kids, text, candle, voice Rec, program
---------------	---

► Funzioni flash

Flash	Auto, auto w/Red-eye reduction, slow sync. w/Red-eye reduction, forced On, Off; flash range: 2.3 m (W), 1.3 m (T)
-------	---

► Interfacce

USB	2.0
Uscita TV	PAL/NTSC

► Alimentazione

Alimentazione	2x AA Alkaline batteries
Spegnimento automatico	1 min., 3 min., 5 min.

► Altro

Dimensioni	approx. 95 x 61 x 24 mm (W x H x L)
Corpo	Highend plastic
Peso	146 g (w/o batteries)
Lingue del menu	English, German, Spanish, French, Italian, Portuguese, Dutch, Swedish, Greek, Czech, Polish, Turkish, Hungarian, Russian, Arabic, Romanian, Thai, Japanese, Simple Chinese, Korean, Traditional Chinese

► Accessori

	USB cable, AV cable, 2 x AA batteries, wrist strap, pouch, CD-Rom
--	---

► Logistica

Numero articolo:	06852
Codice EAN	4004781068521
Dimensioni imballaggio	8.7 x 16.1 x 22.5 cm (W x H x L)
Unità di imballo	5
Peso (imballaggio)	approx. 706 g
Peso/unità imballo	approx. 4.1 kg
Dimensioni/unità imballo	19 x 25 x 46 cm (W x H x L)

Timbro del rivenditore

AgfaPhoto is used under license of Agfa-Gevaert NV&Co. KG. Agfa-Gevaert NV&Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, www.agfaphoto.com
Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com