DC-1338i The intelligent partner

















Technologically superior

- ASM allows to set aperture and shutter speed manually.
- Picture stabiliser reduces risk of blurred images and automatically removes any normal shaking.
- ISO 1600 permits picture-taking with a high sensitivity of up to ISO 1600.
- AF lamp serves to determine the distance in poor lighting conditions so that the subject can be captured sharply.
- **Histogram display** shows the brightness distribution in a view.
- SDHC memory card slot supports cards of the new standard which offer up to 4 GB of extra capacity.



For pictures that inspire

Simply click!

For photos that fulfil high demands. The new DC-1338i is your perfect partner for all photographic challenges and the occasional quick snapshot. The slimline, stylish lightweight made from lacquered matt metal lies well in the hand and is easy to use.

Optimal for every subject

The DC-1338i is excellently equipped for every photo session: with a 10-megapixel CCD sensor, 3x optical and 4x digital zoom, 3-inch TFT colour display with 230,000 pixels and 21 dedicated scene modes. Each setting can be individually selected or configured automatically with the face tracking function for up to three faces per picture. One thing is for sure: with the DC-1338i you have the right tool for the perfect picture.

And there's even more

Whether you want to photograph people, landscapes or moving objects – the DC-1338i is up for the challenge. With the preconfigured scene modes every moment can be captured easily. Simply put: The DC-1338i offers great performance at a sensational price.



Technical Specifications

Picture Sensor

Picture Sensor	
Sensor	10.0 megapixel CCD
▶ Lens	
Lens and typ	6 elements in 5 groups (incl. 3 aspherical lens elements)
Focal length	f = 7.4 (W) ~ 22.2 (T) mm
Equivalent 35mm camera	35.1 (W) ~ 105.3 (T) mm
Brightness	F/2.8 (W), F/5.1 (T)
Shutter speed	1/2000 ~ 8 secs.
Zoom	
Digital zoom/optical zoom	4x/3x
Focussing	
Focus range	T: 50cm ~ infinity, W: 15cm ~ infinity
Display	
Colour display	3.0" TFT LCD, 960 x 240 pixel
File format	
Still images	JPEG, EXIF 2.2, DPOF, PictBridge-compatible
Video/Audio	AVI/WAV
Flash modes	
Flash	Automatic/manual flash, automatic with red-eye reduction,
	low shutter speed synchronisation
Flash range	2.3m (W), 1.3m (T)
Power source	
Power supply	Rechargeable Lithium-Ion battery
Miscellaneous	
Product dimensions	approx. 94 x 20 x 56 mm
Accessories	

USB/AV cable, rechargeable Lithium-ion battery, charging device, pouch, handstrap, CD-ROM

AgfaPhoto accessories Make digital photography complete



AgfaPhoto Recharger Plus – The fast charging device refills your rechargeable batteries easily on the move. Provides for extra-short recharging time.



AgfaPhoto SD Memory Cards – External memory cards with up to 2 GB are especially suitable for action photos and videos.



AgfaPhoto Picture Packs – Your photo lab at home: optimal on photographic paper with special ink, for 100 digital pictures.

More information at www.plawa.com

AgfaPhoto Distributors



AgfaPhoto Printer AP2700 – Compact thermotransfer photo printer. With large colour display, Bluetooth and WiFi options.

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG. Agfa-Gevaert NV & Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice. AgfaPhoto Holding OmbH, www.agfaphoto.com; Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com

