




# DC-733s

7.0 MegaPixel

- ▶ 7.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 2.5" TFT LCD display

## Highlights

- ▶ ISO 1600
- ▶ Face tracking
- ▶ Digital stabilizer
- ▶ Smile detection
- ▶ SDHC compatibility (4 GB)
- ▶ Aperture priority / Shutter priority / Manual exposure mode
- ▶ 16:9 image resolution



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-733s and certified with its logo a rating of 'GOOD'. In detail:

- Handling:	Grade 1.0
- Workmanship:	Grade 1.0
- Instruction manual:	Grade 2.0



- Handling tested
- Instruction manual tested
- Workmanship tested

# DC-733s

## Technical details

### ► Image sensor

Sensor	7.0 megapixel CCD
--------	-------------------

### ► Optics

Lens and type	6 elements in 5 groups
Focal length	f = 6.2 (W) ~ 18.6 (T) mm
Equivalent to 35mm camera	37.5 (W) ~ 112.5 (T) mm)
Brightness	F/ 2.8 (W), 5.2 (T)
Shutter speed	1/2000 ~ 8 sec.

### ► Zoom

Optical zoom	3x
Digital zoom	4x

### ► Focusing

Focus range (normal)	W/T: 80 cm ~ infinity
Focus range (macro)	W: 15 cm ~ infinity, T: 40 cm ~ infinity

### ► Exposure

Exposure compensation	-2 EV to +2 EV in 1/3 step, [-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0]
Exposure meter	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400, 800, 1600
White balance	Auto, daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Exposure control	Automatic/ manual

### ► LCD

Colour	2.5" TFT LCD, 640 x 240
--------	-------------------------

### ► Memory

Memory internal	16 MB
Memory external	SD/SDHC slot up to 4 Gigabyte

### ► Resolution

Still image	3072 x 2304, (3:2) 3072 x 2048, (16:9) 3072 x 1728, 2560 x 1920, 2048 x 1536, 1024 x 768, 640 x 480
Video	720 x 400, 640 x 480, 320 x 240
Video frame rate	30 fps at all resolutions

### ► File formats

Still image	JPEG, EXIF 2.2 compatible format DCF compatible, supp. DPOF, PictBride
Video	AVI w/ audio
Audio	WAV

### ► Scene mode

Scene mode	Program, movie, voice REC, portrait, landscape, sunset, night scene, text, back light, kids, snow, food, fireworks, building, quick mode, smile detection
------------	---

### ► Flash modes

Flash light	Auto, red eye reduction, slow sync., on /off
-------------	--

### ► Interface

USB	2.0
TV out	PAL / NTSC

### ► Power source

Power supply	2 AA batteries
Auto power off	1 min, 3 min, 5 min

### ► Others

Camera dimensions	89 x 27 x 61 (L x B x H) in mm 3,5 x 1,06 x 2,4 (L x W x H) in inch
Body	Highend plastic
Weight	140 g
Menu language	GB, D, E, F, I, P, NL, S, GR, CZ, PL, TR, HU, RUS, KSA, RO, THA, J, CN, ROK

### ► Accessories

Barcode	USB cable, video cable, pouch, batteries, hand strap, CD software
---------	---

### ► Logistik

Item number	06857
Barcode	4004781068576
UPC	884375068571
Packaging size	225 x 87 x 161 (L x B x H) in mm 8,86 x 3,43 x 6,34 (L x W x H) in inch
Packaging unit	5
Weight (packaging)	898 g
Weight (packaging unit)]	5.1 kg
Dimensions packing unit	460 x 250 x 190 (L x B x H) in mm 18,11 x 9,84 x 7,48 (L x W x H) in inch

Dealer stamp

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG. Agfa-Gevaert NV & Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, [www.agfaphoto.com](http://www.agfaphoto.com)  
Manufactured by plawa-feinwerktechnik GmbH & Co. KG, [www.plawa.com](http://www.plawa.com)