


DC-733s

7.0 MegaPixel

- ▶ 7.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 2.5" TFT LCD display

Highlights

- ▶ ISO 1600
- ▶ Face tracking
- ▶ Digital stabilizer
- ▶ Smile detection
- ▶ SDHC compatibility (4 GB)
- ▶ Aperture priority / Shutter priority / Manual exposure mode
- ▶ 16:9 image resolution



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-733s and certified with its logo a rating of 'GOOD'. In detail:

- Handling:	Grade 1.0
- Workmanship:	Grade 1.0
- Instruction manual:	Grade 2.0



- Handling tested
- Instruction manual tested
- Workmanship tested

DC-733s

Caractéristiques techniques

► Capteur d'images

Capteur	7.0 megapixel CCD
---------	-------------------

► Objectif

Objectif et construction	6 elements in 5 groups
Longueur focale	f = 6.2 (W) ~ 18.6 (T) mm
Équivalence caméra 35mm	37.5 (W) ~ 112.5 (T) mm
Vitesse de l'objectif	F/ 2.8 (W), 5.2 (T)
Temps d'obturation	1/2000 ~ 8 sec.

► Zoom

Zoom optique	3x
Zoom numérique	4x

► Mise au point

Focale	W/T: 80 cm ~ infinity
Focale (macro)	W: 15 cm ~ infinity, T: 40 cm ~ infinity

► Exposition

Correction d'exposition	-2 EV to +2 EV in 1/3 step, [-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0]
Variantes d'exposition	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400, 800, 1600
Ance des blancs	Auto, daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Système de mesure de la lumière	Automatic/ manual

► Ecran

Ecran LCD	2.5" TFT LCD, 640 x 240
-----------	-------------------------

► Mémoire

Mémoire interne	16 MB
Mémoire externe	SD/SDHC slot up to 4 Gigabyte

► Résolution

Clichés	3072 x 2304, (3:2) 3072 x 2048, (16:9) 3072 x 1728, 2560 x 1920, 2048 x 1536, 1024 x 768, 640 x 480
Vidéo	720 x 400, 640 x 480, 320 x 240
Fréquence d'images vidéo	30 fps at all resolutions

► Navigations-Features

Clichés	JPEG, EXIF 2.2 compatible format DCF compatible, supp. DPOF, PictBride
Vidéo	AVI w/ audio
Audio	WAV

► Mode de scène

Mode continu	Program, movie, voice REC, portrait, landscape, sunset, night scene, text, back light, kids, snow, food, fireworks, building, quick mode, smile detection
--------------	---

► Fonctions flash

Flash	Auto, red eye reduction, slow sync., on /off
-------	--

► Interfaces

USB	2.0
Sortie TV	PAL / NTSC

► Alimentation

Alimentation	2 AA batteries
Coupage automatique	1 min, 3 min, 5 min

► Divers

Dimesions d'appareil-photo	89 x 27 x 61 (L x B x H) in mm 3,5 x 1,06 x 2,4 (L x W x H) in inch
Boîtier	Highend plastic
Poids	140 g
Langues du menu	GB, D, E, F, I, P, NL, S, GR, CZ, PL, TR, HU, RUS, KSA, RO, THA, J, CN, ROK

► Accessoires

Ci-inclus	USB cable, video cable, pouch, batteries, hand strap, CD software
-----------	---

► Logistique

Réf. article	06857
Code EAN	4004781068576
UPC	884375068571
Emballage de l'appareil photo	225 x 87 x 161 (L x B x H) in mm 8,86 x 3,43 x 6,34 (L x W x H) in inch
Unité de conditionnement	5
Poids (emballage)	898 g
Poids/UC	5.1 kg
Dimensions/ UC	460 x 250 x 190 (L x B x H) in mm 18,11 x 9,84 x 7,48 (L x W x H) in inch

Cachet du revendeur

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG. Agfa-Gevaert NV & Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, www.agfaphoto.com
Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com