DC-8338i The strong all-round talent















For pictures that inspire

Motivates more

What a snapshot that would make! Then it's good that you have the new, light DC-8338i with you. With the handy 128g model you are equipped for any situation. And it's not only its technology that cuts a good figure – the outside also looks pretty smart. The attractive, lacquered matt metallic housing underscores the elegance and the state-of-the-art design of the camera.

Picture for picture, the best quality

Packed full of great features, the DC-8338i, with its 8.0-megapixel CCD sensor, 3x optical and 4x digital zoom, 3-inch TFT colour display with 230,000 pixels and sophisticated scene modes simply offers a greatvalue. With 10 digital frame options available, your pictures can be framed on the fly.

More performance built-in

You can always rely on the DC-8338i. Whether it's adverse weather conditions, twilight or a subjects in motion, capture every moment easily – just as you want. Because with the DC-8338i you will always be on the safe side and able to take perfect pictures. The excellent price-performance ratio speaks for itself.



Perfect in every detail

- ASM allows to set aperture and shutter speed manually.
- Picture stabiliser reduces risk of blurred images and automatically removes any normal shaking.
- Face tracking offers automatic face recognition for up to three faces and simultaneously sets a suitable exposure.
- ISO 1600 permits picture-taking with a high sensitivity of up to ISO 1600.
- AF lamp serves to determine the distance in poor lighting conditions so that the subject can be captured sharply.
- **Histogram display** shows the brightness distribution in a view.
- SDHC memory card slot supports cards of the new standard which offer up to 4 GB of extra capacity.



Technical Specifications

Picture Sensor

Ficture Sensor	
Sensor	8.0 megapixel CCD
Lens	
Lens and typ	6 elements in 5 groups (incl. 3 aspherical lens elements)
Focal length	f = 6.2 (W) ~ 18.6 (T) mm
Equivalent 35mm camera	37.5 (W) ~ 112.5 (T) mm
Brightness	F/2.8 (W), F/5.2 (T)
Shutter speed	1/2000 ~ 8 secs.
Zoom	
Digital zoom/optical zoom	4x/3x
Focussing	
Focus range	T: 40cm ~ infinity, W: 15cm ~ infinity
Display	
Colour display	3.0" TFT LCD, 960 x 240 pixel
File format	
Still images	JPEG, EXIF 2.2, DPOF, PictBridge-compatible
Video/Audio	AVI/WAV
Flash modes	
Flash	Auto, auto w/Red-eye reduction, slow sync. w/Red-eye reduction,
	forced On, Off
Flash range	2.3m (W), 1.3m (T)
Power source	
Power supply	Rechargeable Lithium-Ion battery
Miscellaneous	
Product dimensions	approx. 95 x 18 x 55 mm
Accessories	

USB/AV cable, rechargeable Lithium-ion battery, charging device, pouch, hand strap, CD-ROM

AgfaPhoto accessories Make digital photography complete



AgfaPhoto Recharger Plus – The fast charging device refills your rechargeable batteries easily on the move. Provides for extra-short recharging time.



AgfaPhoto SD Memory Cards – External memory cards with up to 2 GB are especially suitable for action photos and videos.



AgfaPhoto Picture Packs – Your photo lab at home: optimal on photographic paper with special ink, for 100 digital pictures.

More information at www.plawa.com

AgfaPhoto Distributors

AgfaPhoto Printer AP2700 – Compact thermotransfer photo printer. With large colour display, Bluetooth and WiFi options.

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG. Agfa-Gevaert NV & Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice. AgfaPhoto Holding OmbH, www.agfaphoto.com; Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com

