


DC-833m

8.0 MegaPixel

- ▶ 8.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 2.5" TFT LCD
- ▶ 16 scene modes
- ▶ Movie recording with sound
- ▶ 16 MB internal memory
- ▶ SDHC card format
- ▶ 2 AA batteries

Highlights

- ▶ Smile detection
- ▶ Face tracking
- ▶ Digital stabilizer
- ▶ Red eye removal



DC-833m

Technical details

► Image sensor

| | |
|---------------|-------------------|
| Lens and type | 8.0 MegaPixel CCD |
|---------------|-------------------|

► Optics

| | |
|---------------------------|---------------------------|
| Lens and type | 6 elements in 5 groups |
| Focal length | f = 6.2 (W) ~ 18.6 (T) mm |
| Equivalent to 35mm camera | 37.5 (W) ~ 112.5 (T) mm |
| Brightness | F/ 2.8 (W), 5.2 (T) |
| Shutter speed | 1/2000 ~ 8 sec. |

► Zoom

| | |
|--------------|----|
| Optical zoom | 3x |
| Digital zoom | 4x |

► Focusing

| | |
|-------------|--|
| Focus range | 15 cm ~ infinity (W), 40 cm ~ infinity (T) |
|-------------|--|

► Exposure

| | |
|-----------------------|--|
| Exposure compensation | -2 EV to +2 EV in 0.5 steps, (-2.0, -1.5, -1.0, -0.5, 0.0, +0.5, +1.0, +1.5, +2.0) |
| Exposure metering | Center, multi, spot |
| ISO | Automatic, 100, 200, 400, 800, 1600, |
| White balance | Automatic, daylight, cloudy, tungsten, fluorescent |

► LCD

| | |
|--------|----------------------|
| Colour | 2.5" TFT LCD display |
|--------|----------------------|

► Memory

| | |
|-----------------|---|
| Memory internal | 16 MB |
| Memory external | SD card: up to 4 GB; SDHC card: up to 16 GB |

► Resolution

| | |
|------------------|---|
| Still image | 3264 x 2448, 3264 x 2176 (3:2) 3264 x 1840 (16:9), 2816 x 2112, 2272 x 1704, 1600 x 1200, 640 x 480 |
| Video | 720 x 400 (16:9), 640 x 480, 320 x 240 |
| Video frame rate | 30 fps |

► File formats

| | |
|-------------|--|
| Still image | JPEG (EXIF 2.2 compatible), DCF format DPOF compatible |
| Video | MJPEG w/audio |
| Audio | WAV |

► Scene modes

| | |
|-------------|--|
| Scene modes | Program, movie, voice recording, portrait, landscape, sunset, night scene, text, backlight, kids, snow, food, fireworks, building, quick mode, smile detection |
|-------------|--|

► Flash modes

| | |
|-------------|--|
| Flash light | Automatic, red eye reduction, slow sync., on / off |
| Flash range | 2.5 (W), 1.5 (T) |

► Interfaces

| | |
|---------|------------|
| USB 2.0 | Full speed |
| TV out | PAL / NTSC |

► Power source

| | |
|----------------|---------------------|
| Power supply | 2 AA batteries |
| Auto power off | 1 min, 3 min, 5 min |

► Others

| | |
|-------------------|-------------------------|
| Camera dimensions | Approx. 89 x 27 x 61 mm |
| Body | Highend plastic |
| Weight | 120 g |

► Accessories

| | |
|-------------|--|
| Accessories | USB & AV cable, pouch, batteries, hand strap, CD software, quick guide |
|-------------|--|

► Logistics

| | |
|-----------------------------|----------------------|
| Item number | 06915 |
| Bar code | 4004781069153 |
| UPC code | 884375069158 |
| Packaging size | 8.7 x 16.1 x 22.5 cm |
| Packaging unit | 5 |
| Weight (packaging) | TBD |
| Weight (packaging unit) | TBD |
| Dimensions (packaging unit) | TBD |

Dealer stamp

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG or Agfa-Gevaert NV. Agfa-Gevaert NV & Co. KG or Agfa-Gevaert does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.

AgfaPhoto Holding GmbH, www.agfaphoto.com
 Manufactured by plawa-feinwerktechnik GmbH & Co. KG, www.plawa.com