



Digitalkamera

OPTIMA 3

14.0
MP

8X
Optical
zoom

28 mm
Wide
angle

3.0"
LCD

HD

Face
tracking

OIS
Stabiliser

HDR
Image

Smile
detection

Metal
body

- 14.0 MegaPixel CCD Sensor
- 8x optischer Weitwinkelzoom
(28 ~ 224 mm äquivalent 35 mm)
- 7.6 cm (3.0") TFT LCD Display
- Panorama Modus
- Intelligenter Szenemodus
- HD Video (1280 x 720)
- Optischer Bildstabilisator (OIS)



OPTIMA 3

Technische Daten

- 14.0 MegaPixel CCD Sensor
- 8x optischer Weitwinkelzoom (28 ~ 224 mm äquivalent 35 mm)
- 6x Digitalzoom
- 7.6 cm (3.0") TFT LCD Display
- Panorama Modus
- Intelligenter Szenemodus
- HD Video (1280 x 720)
- Optischer Bildstabilisator (OIS)



Bildsensor

Sensor 14.0 MegaPixel CCD sensor

Objektiv

Linse 12 elements in 8 groups
 Brennweite f = 5.1 (W) ~ 40.8 (T) mm
 Äquivalent 35mm Kamera 28 (W) ~ 224 (T) mm
 Lichtstärke F/ 3.3 (W), 5.8 (T)
 Verschlusszeit 4 ~ 1/2000 second, (Manual 30 sec)

Zoom

Optischer Zoom, Digitalzoom 8x, 6x

Fokussierung

Fokusreichweite (Normal) 60 cm ~ infinity (W), 100 cm ~ infinity (T)
 Fokusreichweite (Macro) 5 cm ~ infinity (Wide only)

Belichtung

Belichtungsausgleich -2 EV to +2 EV in 1/3 steps
 Artificial Intelligence AE (AiAE), center-weighted average, spot (Fixed to center of frame)
 Program AE (AE-lock available)
 Belichtungsvarianten Auto, 80, 100, 200, 400, 800, 1600, 3200
 Belichtungskontrolle ISO Automatic (AWB), daylight, cloudy, fluorescent, CWF, incandescent, manual
 Weißabgleich

Display

Display 3.0" TFT LCD display
 Auflösung 960 (W) x 240 (H)

Speichermedium

Interner Speicher 32 MB
 Externer Speicher SD card / SDHC card (Up to 16 GB support)

Auflösung

Bild 14 MP: 4320 x 3240, 10 MP: 4320 x 2880 (3:2), 10 MP: 4320 x 2432 (16:9), 8 MP: 3264 x 2448, 5 MP: 2592 x 1944, 3 MP: 2048 x 1536, 2 MP: 1920 x 1080, 0.3 MP: 640 x 480
 Video 1280 x 720, 640 x 480, 320 x 240
 Bildwiederholrate 30 fps, 15 fps

Dateiformat

Bild JPEG (EXIF 2.2 compatible), DCF, DPOF (Ver1.1)
 Video MPEG-4/ H.264

Blitzfunktion

Blitzlicht Automatic, red eye reduction, red eye reduction & slow sync, forced flash, slow sync, on/ off
 Blitzreichweite Approx. 0.3 m ~ 5.1 m (W)/ approx. 1.0 m ~ 2.8 m (ISO 800) (T)

Motivmodus

Motivmodi Automatic, intelligent scene modes, manual, sport, indoor, snow, fireworks, museum, night landscape, children, leaf, sunset, glass, landscape, night portrait, portrait, panorama, video

Schnittstellen

USB 2.0 Full speed
 TV-out PAL/ NTSC
 HDTV-out Supported

Stromversorgung

Stromversorgung Lithium-ion battery (D016, 3.7V 700 mAh)
 Automatisches Abschalten 1 min., 3 min., 5 min.

Sonstiges

Abmessung 98.5 x 57.3 x (21~24.8) mm
 Gehäuse Metal
 Gewicht 146 g

Enthaltenes Zubehör

Standard USB cable, lithium-ion battery, battery charger, power cord, hand strap, CD-Rom software, quick guide

Logistik

Artikelnummer 07003
 Barcode 4004781070036
 UPC Code 884375070031
 Verpackung 145 x 140 x 58 mm
 VPE 10
 Gewicht (Verpackung) approx. 430 g
 Gewicht (VPE) approx. 4.73 kg
 Dimensionen approx. 32.5 x 29.5 x 18.5 cm

Händlerstempel

AgfaPhoto is used under license of Agfa-Gevaert NV & Co. KG or Agfa-Gevaert NV. Neither Agfa-Gevaert NV & Co. KG nor Agfa-Gevaert NV manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.